




Poles	Tolerance
1p-6p	±0.10
7p-12p	±0.20
13p-18p	±0.30
19p-24p	±0.40

Material:	
Contact Solder Pin:	Brass, Tin Plated
Wire Retention Spring:	Stainless Steel
Insulating Body:	Polyamide, UL94V-0
Electrical	
Voltage Rating:	300 VAC
Current rating (solid):	13 AMPS
Current rating (stranded):	16 AMPS
Withstand Voltage:	1500 VAC, Test time 60 sec
Wire Range (solid):	14-24 AWG
Wire Range (stranded):	12-24 AWG
Mechanical	
Operating Temperature:	-40°C to +115°C -40°F to +239°F
Soldering Temperature:	260°C, 500°F for 5 seconds
Safety Approval:	UL US



N=Number of Positions



P.C.B. Layout


Part Number Configuration.

EB1088-XX-X02

Number of Positions

Color Option:  
0-Black  
2-Red  
3-Orange  
4-Yellow  
5-Green  
6-Blue  
8-Gray  
9-White

Max Number of Positions = 24

UNLESS OTHERWISE SPECIFIED BREAK ALL SHARP EDGES AND DEBURR ALL HOLES	TITLE: 5.00mm SPACING, SCREWLESS BLOCK HORIZONTAL ALIGNMENT
LIMITS: UNLESS OTHERWISE SPECIFIED HUND.±.02 FRACT.±1/64 THOU.±.005 ANGLE±1°	SCALE THIS IS A CONFIDENTIAL DRAWING AND MUSTBE TREATED AS SUCH. NO DISTRIBUTION IS ALLOWED WITHOUT WRITTEN APPROVAL BY EBY ELECTRO INC.
	
PLAINVIEW, NY 11803	

IMPORTANT DISCLAIMER: All information provided on this print is for reference. Always perform your own tests and acquire samples and further information to determine product suitability. While we make effort to provide accurate information, we cannot be responsible for errors either of omission or typographical. EBY Electro, Inc. assumes no responsibility for the use or suitability of any product. All products and specifications are subject to change without prior written notice.

METRIC LIMITS ONE PLACE ±0.3 TWO PLACES ±0.10 ANGLE ± 1°	DRAWN AJT CHECKED APPROVED	DATE 08/03/16 DATE DATE	SIZE A	DRAWING NUMBER: EB1088-XX-X02	REV.
---	----------------------------------	-------------------------------	-----------	----------------------------------	------