




RoHS Compliant

Rev.	ECO#	Date	By
B	1143-0916	09/15/16	AJT



N=Number of Positions



Material:	
Contact Clip:	Brass, Tin Plated
Terminal Screw:	M3, Steel, Zinc Plating, "-" Slotted
Flange Screw:	M3, Steel, Zinc Plating, "x" Slotted
Insulating Body:	Polyamide, UL94V-0, Green
Electrical	
Voltage Rating:	300 VAC
Current rating:	20 AMPS
Wire Range:	10-30 AWG
Withstand Voltage:	1500 VAC, Test time 60 seconds
Mechanical	
Torque:	4.5 lb-in Max.
Operating Temperature:	-40°C to +115°C -40°F to +239°F
Soldering Temperature:	260°C, 500°F for 5 seconds max.
Safety Approval:	UL US


Part Number Configuration.

EB1768M-XX-500

Number of Positions: X
Color: 5-Green

(Other Color Options Available)
(Please consult Factory)

Max Number of Positions = 16

UNLESS OTHERWISE SPECIFIED BREAK ALL SHARP EDGES AND DEBURR ALL HOLES	TITLE: 7.62mm SPACING, PLUGGABLE BLOCK WITH MOUNTING FLANGES
LIMITS: UNLESS OTHERWISE SPECIFIED HUND.±.02 FRACT.±1/64 THOU.±.005 ANGLE±1°	SCALE THIS IS A CONFIDENTIAL DRAWING AND MUSTBE TREATED AS SUCH. NO DISTRIBUTION IS ALLOWED WITHOUT WRITTEN APPROVAL BY EBY ELECTRO INC.
 PLAINVIEW, NY 11803	

IMPORTANT DISCLAIMER: All information provided on this print is for reference. Always perform your own tests and acquire samples and further information to determine product suitability. While we make effort to provide accurate information, we cannot be responsible for errors either of omission or typographical. EBY Electro, Inc. assumes no responsibility for the use or suitability of any product. All products and specifications are subject to change without prior written notice.

METRIC LIMITS ONE PLACE ±0.3 TWO PLACES ±0.10 ANGLE ±1°	DRAWN JM CHECKED APPROVED	DATE 10/20/08 DATE DATE	SIZE A	DRAWING NUMBER: EB1768M-XX-500	REV. B
--	---------------------------------	-------------------------------	-----------	-----------------------------------	-----------