



Rev.	ECO#	Date	Ву

N=NUMBER OF CONTACTS

DIM		TOL				
	DIN	1P	2P	3P4P	5P8P	9P12P
Dim A	N*10.0	±0.20	±0.40	±0.40	±0.50	±0.60
Dim B	(N-1>*10.0	/	±0.20	±0.40	±0.50	±0.60






Material:			
Contact:	Copper, Matte Tin over Ni Plating		
Wire Retention Spring:	Stainless Steel		
Lever:	Thermoplastic, UL94V-0, White, RAL9003		
Insulating Body:	Thermoplastic, UL94V-0		
Elect	rical		
Voltage Rating:	300 VAC		
Current rating:	55 AMPS		
Withstand Voltage:	1600 VAC, Test time 60 sec		
Wire Range:	6-16 AWG		
Mech	anical		
Wire Strip Length:	12-13mm		
Operating Temperature:	-40°C to +115°C -40°F to +239°F		
Soldering Temperature:	260°C, 500°F for 5 seconds		
Safety Approval:	c Fl us		

10.00 3.81 3.10 50 DIM A

PCB Layout

Part Number Configuration.



2 Red (RAL3001/D) 3 Orange(RAL2011/P)

4 Yellow(RAL1018/A)

5 Green(RAL6018/T)

6 Blue (RAL5015/A)

8 Grey(RAL7004/P)

9 White(RAL1102)

TITLE: UNLESS OTHERWISE SPECIFIED BREAK ALL SHARP EDGES AND DEBURR ALL HOLES

10.00mm Spacing, Modular

LIMITS: UNLESS SCALE THIS IS A CONFIDENTIAL DRAWING AND OTHERWISED SPECIFIED MUSTBE TREATED AS SUCH. NO HUND.±.02 FRACT.±1/64 DISTRIBUTION IS ALLOWED WITHOUT ANGLE±1° TH0U.±.005 WRITTEN APPROVAL BY EBY ELECTRO INC

Electro Inc. PLAINVIEW, NY 11803

IMPORTANT DISCLAIMER: All information provided on this print is for reference. Always perform your own tests and acquire samples | METRIC LIMITS and further information to determine product suitability. While we make effort to provide accurate information, we cannot be ONE PLACE 10.3 responsible for errors either of omission or typographical. EBY Electro, Inc. assumes no responsibility for the use or suitability of any product. All products and specifications are subject to change without prior written notice.

MWP DRAWN CHECKED **APPROVED**

DATE 08/29/18 DATE DATE

SIZE

EB4210-XX-X00

REV.