

Material:	
Contact Retention Spring:	Brass, (CuZn)
Contact Clip:	PhBz (CuSn)
Insulating Body:	Polyamide, UL94V-0, Green
Electrical	
Voltage Rating:	300 VAC
Current rating:	10 AMPS
Withstand Voltage:	1500 VAC, Test time 60 sec
Wire Range:	12-26 AWG
Mechanical	
Operating Temperature:	-40°C to +105°C -40°F to +221°F
Safety Approval:	UL US


Part Number Configuration.

EB460B-XX-500

Number of Positions

(Other Color Options Available)
(Please consult Factory)

IMPORTANT DISCLAIMER: All information provided on this print is for reference. Always perform your own tests and acquire samples and further information to determine product suitability. While we make effort to provide accurate information, we cannot be responsible for errors either of omission or typographical. EBY Electro, Inc. assumes no responsibility for the use or suitability of any product. All products and specifications are subject to change without prior written notice.

UNLESS OTHERWISE SPECIFIED BREAK ALL SHARP EDGES AND DEBURR ALL HOLES		TITLE: 5.00mm SPACING, MATING END ON BACK SIDE SCREWLESS PLUGGABLE BLOCK	
LIMITS: UNLESS OTHERWISE SPECIFIED HUND. ±.02 THOU. ±.005	FRACT. ±1/64 ANGLE ±1°	SCALE	THIS IS A CONFIDENTIAL DRAWING AND MUSTBE TREATED AS SUCH. NO DISTRIBUTION IS ALLOWED WITHOUT WRITTEN APPROVAL BY EBY ELECTRO INC.
METRIC LIMITS ONE PLACE ±0.3 TWO PLACES ±0.10 ANGLE ± 1°	DRAWN JM CHECKED APPROVED	DATE 11/18/09 DATE DATE	SIZE A DRAWING NUMBER: EB460B-XX-500
 EBY Electro Inc. PLAINVIEW, NY 11803		REV.	