



SECTION P-P

Material:	
Wire Guard:	Stainless Steel
Contact Pin:	PhBz, Tin Plated
Mounting Flange Nut:	Brass, M2.5
Insulating Body:	Polyamide, UL94V-0
Electrical	
Voltage Rating:	300 VAC
Current rating:	4 AMPS
Withstand Voltage:	1500 VAC, Test time 60 sec
Wire Range:	16-28 AWG
Mechanical	
Operating Temperature:	-40°C to +115°C -40°F to +240°F
Safety Approval:	C US

Part Number Configuration.

EB475MN-XX-500

Number of Positions Color
5 5-Green

(Other Color Options Available)
(Please consult Factory)

Max Number of Positions = 24

N = Number of poles

UNLESS OTHERWISE SPECIFIED BREAK ALL SHARP EDGES AND DEBURR ALL HOLES	TITLE: 3.81mm SPACING	
	SCREWLESS PLUGGABLE BLOCK	
LIMITS: UNLESS OTHERWISE SPECIFIED HUND.±.02 FRACT.±1/64 THOU.±.005 ANGLE±1°	SCALE	THIS IS A CONFIDENTIAL DRAWING AND MUSTBE TREATED AS SUCH. NO DISTRIBUTION IS ALLOWED WITHOUT WRITTEN APPROVAL BY EBY ELECTRO INC.
		PLAINVIEW, NY 11803

IMPORTANT DISCLAIMER: All information provided on this print is for reference. Always perform your own tests and acquire samples and further information to determine product suitability. While we make effort to provide accurate information, we cannot be responsible for errors either of omission or typographical. EBY Electro, Inc. assumes no responsibility for the use or suitability of any product. All products and specifications are subject to change without prior written notice.

METRIC LIMITS ONE PLACE ±0.3 TWO PLACES ±0.10 ANGLE ±1°	DRAWN AJT	DATE 07/30/14	SIZE A	DRAWING NUMBER: EB475MN-XX-500	REV.
	CHECKED	DATE			
	APPROVED	DATE			