

P.C.B
Layout

Material:	
Contact Solder Pin:	Copper, Matte Tin Plated
Insulating Body:	LCP, UL94V-0
Electrical	
Voltage Rating:	150 VAC
Current rating:	5.5 AMPS
Withstand Voltage:	1300 VAC, Test time 60 seconds
Mechanical	
Operating Temperature:	-40°C to +65°C -40°F to +149°F
Soldering Temperature:	260°C, 500°F for 10 seconds max.
Safety Approval:	


Part Number Configuration.

VC5350-XX-X00

Number of Color
Positions 0-Black

(Other Color Options Available)
(Please consult Factory)

MAX NUMBER OF POSITIONS = 48 (2x24)

UNLESS OTHERWISE SPECIFIED SHARP EDGES AND DEBURR ALL HOLES	TITLE: 3.50mm SPACING, PLUGGABLE HEADER VERTICAL, CLOSED	
	LIMITS: UNLESS OTHERWISE SPECIFIED HUND.±.02 FRACT.±1/64 THOU.±.005 ANGLE±1°	SCALE THIS IS A CONFIDENTIAL DRAWING AND MUSTBE TREATED AS SUCH. NO DISTRIBUTION IS ALLOWED WITHOUT WRITTEN APPROVAL BY EBY ELECTRO INC.
		PLAINVIEW, NY 11803